

TRV-HD



ROV General Specifications:

Depth Rating	3300 ft. (1000m) standard (deeper options)
Payload	300 lbs. (136 kg)
Height	36 in. (914 mm)
Length	67 in. (1700 mm)
Width (forward)	54.5 in. (1384 mm)
Weight in Air	1150 lbs. (2530kg)

Maximum Static Thrust:

Forward	460 lbs.
Reverse	300 lbs.
Lateral	110 lbs.
Vertical	230 lbs.

Maximum Velocity: (100 ft. tether excursion)

Forward	1.53 m/s (3 kts)
Reverse	1.02 m/s (2 kts)
Lateral	.75 m/s (1.5 kts)
Vertical	Up to 2'/sec
Turning Rate	120° per second max.

Surface Control Unit:

Height	12.28 in. (312 mm)
Width	16.50 in. (419 mm)
Depth	22.25 in. (565 mm)
Weight	291 lbs. (132 kg)
SCU Power Requirements	220 VAC 3Ø 15kw

Tether Dimensions:

Tether (standard length- live boat mode)	1500 ft. (500 m)
Diameter	22.5 mm (.886 in.)
Weight in Air	345 lb/kft (513 kg/km)
Weight in Seawater	71 lb/kft (106 kg/km)
Breaking Load	2500 lbf (11.2 kN)

Thruster Technology:

Brushless DC motors with internal drive modules.

Chassis:

T6061 Aluminum

Buoyancy:

1000m Syntactic Foam (standard, deeper options available)

Hand Control Unit:

Height	3.25 in.
Width	8.5 in.
Length	12.0 in.
Weight	5.0 lbs. (2.27 kg)

Hand Control Functions:

Thruster Control: Fore, Aft, Lateral, Vertical (Normal),
Vertical (Pitch), Rotate
0-100% Gain Control on Port, Stb. & Lateral
0-100% Gain Control on Verticals
0-100% Gain Control on Forward Bias
Auto Depth, Auto Heading, Auto Altitude
Thruster enable/disable

Cameras: Pan, Tilt, Zoom & Focus on Colour Camera
Pan, Tilt on B/W Camera
Remote Control for Rotate Colour Camera

Manipulator: Swing Left/Right
Upper Arm Up/Down
Lower Arm Up/Down
Jaw Rotate CW/CCW
Jaw Open/Close

HPU Select Pump 1, Pump 2

Lights: 2 x LED Light potentiometers 0-100% intensity

Remote Hand Control Unit:

Height	2.25 in.
Width	7.75 in.
Depth	4.75 in.
Weight	1.0 lbs.

Remote Hand Control Functions:

Thruster Control: Fore, Aft, Lateral, Vertical, Rotate, Thruster
Enable/Disable Switch. Lights: On/Off (Full Intensity)

Sonar:

MS 1000 Sonar Head

Modular Components:

Telemetry Can, Power Can, Capacitor Bottle, 2 x HPU's,
2 x 7 Function Valve Packs

Navigation:

Gyro/Fluxgate Combination w/pitch & roll

Lighting:

4 x LED High Power Light Systems

Auto Functions:

Auto Depth, Heading & Altitude

Cameras: 4

Sony Color Zoom, Focus, Pan & Tilt
Low Light B/W, Pan & Tilt
Rotary Color 360° Viewing
B/W Manip Camera

Cameras on two Video CCT's (any combination of two cameras can
be viewed at any time)