

# TRV-M



## General Specifications:

Depth Rating	3300 ft. (1000m) standard (deeper options)
Payload	60 lbs. (27 kg)
Height	24 in. (610 mm)
Length	60 in. (1524 mm)
Width (forward)	36 in. (914 mm)
Width (aft)	48 in. (1219 mm)
Weight in Air	650 lbs. (295 kg)

## Maximum Static Thrust:

Forward	230 lbs.
Reverse	150 lbs.
Lateral	110 lbs.
Vertical	230 lbs.

## Maximum Velocity: (100 ft. tether excursion)

Forward	2.04 m/s (4 kts)
Reverse	1.53 m/s (3 kts)
Lateral	1.02 m/s (2 kts)
Vertical	Up to 3 m/s
Turning Rate	120° per second max.

## Surface Control Unit:

Height	12.28 in. (312 mm)
Width	16.50 in. (419 mm)
Depth	22.25 in. (565 mm)
Weight	291 lbs. (132 kg)
SCU Power Requirements	220 VAC 3Ø 15kw

## Tether Dimensions:

Tether (standard length- live boat mode)	1500 ft. (500 m)
Diameter	22.5 mm (.886 in.)
Weight in Air	345 lb/kft (513 kg/km)
Weight in Seawater	71 lb/kft (106 kg/km)
Breaking Load	2500 lbf (11.2 kN)

## Thruster Technology:

5 x Brushless DC motors with internal drive modules.

## Chassis:

T6061 Aluminum

## Buoyancy:

1000m Syntactic Foam (standard, deeper options available)

## Hand Control Unit:

Height	3.25 in.
Width	8.5 in.
Length	12.0 in.
Weight	5.0 lbs. (2.27 kg)

## Hand Control Functions:

Thruster Control:	Fore, Aft, Lateral, Vertical (Normal), Vertical (Pitch), Rotate 0-100% Gain Control on Port, Stb. & Lateral 0-100% Gain Control on Verticals 0-100% Gain Control on Forward Bias Auto Depth, Auto Heading, Auto Altitude Thruster enable/disable Normal/Pitch Mode Switch
Cameras:	Pan, Tilt, Zoom & Focus on Colour Camera (primary) Pan, Tilt on B/W Camera (primary) Remote Control for Colour Camera (secondary)
Manipulators:	Swing Left/Right Arm Up/Down Jaw Rotate CW/CCW Jaw Open/Close
Lights:	2 x LED Light potentiometers 0-100% intensity

## Remote Hand Control Unit:

Height	2.25 in.
Width	7.75 in.
Depth	4.75 in.
Weight	1.0 lbs.

## Remote Hand Control Functions:

Thruster Control: Fore, Aft, Lateral, Vertical, Rotate, Thruster Enable/Disable Switch. Lights: On/Off (Full Intensity)

## Sonar:

MS 1000 Sonar Head

## Modular Components:

Telemetry Can, Power Can, Capacitor Bottle, HPU, 2 x 4-Function Valve Pack

## Navigation:

Gyro/Fluxgate Combination w/pitch & roll.

## Lighting:

4 x LED High Power Light Systems

## Auto Functions:

Auto Depth, Heading & Altitude

## Cameras: 4

Sony Color Zoom, Focus, Pan & Tilt  
Low Light B/W, Pan & Tilt  
Rotary Color 360° Viewing  
B/W Manip Camera  
Cameras on two Video CCT's (any combination of two cameras can be viewed at any time)